## **Electric Parallel Grippers** EIG2-40140 2-Finger

- Compact size
   Slim rectangular body with five installation positions for flexible mounting
   Grip control: force and position adjustment

- Grip control: force and position adjustment
   Quick open/close time with speed adjustment
   Grip feedback and part detection: gripper status can be read at the PLC/Controller and visualized on the unit via LED's
   Multiple communication modes: the gripper supports Modbus RTU protocol and IO mode control. Other protocols such as USB and ETHERNET can be implemented through a protocol converter.
   Grip actuation via embedded controller.



#### **SPECIFICATIONS**

Model	Stroke per Jaw	Gripping Force per Jaw	Total Gripping Force	Opening/ Closing Time	Nominal Voltage	Nominal Current		Repeatability (Positioning)	Recommended Workpiece Weight*	Weight (fingers excluded)
EIG2-40140	40 mm		80 - 280 N	0.7 / 0.7 s	24 V DC ± 10%	0.50 A	1.20 A	± 0.03 mm	3.00 kg	1.00 kg
	1.57 in	8.99 - 31.47 lb	17.98 - 62.95 lb					± 0.001 in	6.61 lb	2.20 lb


<sup>\*</sup> Recommended workpiece weight depends on the shape of the part, the material and friction of the contact surface and the acceleration of the motion.

Communication Interface Standard: Modbus RTU (RS485), Digital I/O Optional: TCP/IP, USB2.0, CAN2.0A, PROFINET, EtherCAT

#### IP Protection Class IP 54

Noise Emission (Sound Pressure)  $\leq$  40 dB(A) in any direction Recommended operating environment 0-40 °C (32-104 °F), < 85% RH

For this type of gripper the use of the standard fingers is recommended.





# Fz 300 N (67.44 lb) Mx 7 Nm (61.96 in-lb) My 7 Nm (61.96 in-lb) Mz 7 Nm (61.96 in-lb)





### **PRODUCT INFORMATION**

### EIG2-40140 2-Finger











Applied Robotics Inc.
648 Saratoga Road
Glenville, NY 12302 USA
Tel. +1 518 384 1000 Fax +1.5183841200
info@appliedrobotics.com
www.appliedrobotics.com



EFFECTO GROUP S.p.A.
Via Roma, 141/143
28017 San Maurizio d'Opaglio (NO) - Italy
Tel. +39 0322 96142 Fax +39 0322 967453
info@effectogroup.com
www.effecto.com

