

1)_NORMA_1	DIN-EN 857 2SC
2)_NORMA_2	
3)_SOTTOSTRATO	GOMMA SINTETICA
4)_RINFORZO	2 TRECCIE D' ACCIAIO
5)_COPERTURA	GOMMA SINTETICA
6)_TEMPERATURA ESERCIZIO	-40°C +100
7)_NOTE	

R2K/W



CODART	DN_P	DN_mm	DI	DR	DE	WP_bar	BP_bar	P_kg/mt	Rc_mm
R2K-04/W	1/4"	6	6,4		13,8	400	1600	0,280	75
R2K-05/W	5/16"	8	7,9		15,6	350	1400	0,330	85
R2K-06/W	3/8"	10	9,5		17,7	330	1320	0,420	90
R2K-08/W	1/2"	12	12,7		21,0	275	1100	0,510	130
R2K-10/W	5/8"	16	15,9		24,3	250	1000	0,600	170
R2K-12/W	3/4"	19	19,0		28,0	215	860	0,790	200
R2K-16/W	1"	25	025		036	0165	0660	1,130	250

1)_NORMA_1	SAE100 R1A T
2)_NORMA_2	DIN20022 1SN
3)_SOTTOSTRATO	GOMMA SINTETICA
4)_RINFORZO	1 TRECCIA D' ACCIAIO
5)_COPERTURA	GOMMA SINTETICA
6)_TEMPERATURA ESERCIZIO	-40°C +100°C
7)_NOTE	TUBO RIVESTITO TRECCIA INOX

R1T(T)



CODART	DN_P	DN_mm	DI	DR	DE	WP_bar	BP_bar	P_kg/mt	Rc_mm
R1T(T)-03	3/16"	5	4,8			250	1150	0,190	90
R1T(T)-04	1/4"	6	6,4			225	1000	0,240	100
R1T(T)-05	5/16"	8	7,9			215	950	0,280	115
R1T(T)-06	3/8"	10	9,5			180	800	0,330	130
R1T(T)-08	1/2"	12	12,7			160	680	0,420	180
R1T(T)-10	5/8"	16	15,9			130	600	0,490	200
R1T(T)-12	3/4"	20	19,0			105	500	0,620	240
R1T(T)-16	1"	25	25,4			90	360	0,940	300
R1T(T)-20	1.1/4"	32	31,8			65	375	1,280	420

- 1)_NORMA_1
2)_NORMA_2
3)_SOTTOSTRATO
4)_RINFORZO
5)_COPERTURA
6)_TEMPERATURA ESERCIZIO
7)_NOTE

SAE100 R2AT
DIN20022 2SN
GOMMA SINTETICA
2 TRECCE D' ACCIAIO
GOMMA SINTETICA
-40°C +100
TUBO RIVESTITO TRECCIA INOX -

R2T(T)



CODART	DN_P	DN_mm	DI	DR	DE	WP_bar	BP_bar	P_kg/mt	Rc_mm
R2T(T)-03	3/16"	5	4,8			415	2000	0,320	90
R2T(T)-04	1/4"	6	6,4			400	1750	0,370	100
R2T(T)-05	5/16"	8	7,9			350	1480	0,410	115
R2T(T)-06	3/8"	10	9,5			330	1400	0,530	130
R2T(T)-08	1/2"	12	12,7			275	1170	0,640	180
R2T(T)-10	5/8"	16	15,9			250	1020	0,740	200
R2T(T)-12	3/4"	19	19,0			215	900	0,920	240
R2T(T)-16	1"	25	25,4			175	670	1,350	300
R2T(T)-20	1.1/4"	31	31,8			140	600	2,000	420

- 1)_NORMA_1
2)_NORMA_2
3)_SOTTOSTRATO
4)_RINFORZO
5)_COPERTURA
6)_TEMPERATURA ESERCIZIO
7)_NOTE

GOST-R
GOMMA SINTETICA OLEORESISTENTE
2 TRECCE ACCIAIO
GOMMA SINTETICA ANTIABRASIONE
-40 + 125 C°

ROCKMASTER2PLUS



CODART	DN_P	DN_mm	DI	DR	DE	WP_bar	BP_bar	P_kg/mt	Rc_mm
ROCKMASTER2PLUS-06	3/8"	10	9,5	16,7	18,5	400	1600	0,525	127
ROCKMASTER2PLUS-08	1/2"	12	12,7	20,1	22,1	295	1180	0,745	178
ROCKMASTER2PLUS-10	5/8"	16	15,9	23,2	25,2	340	1360	0,870	200
ROCKMASTER2PLUS-12	3/4"	20	19,0	27,1	29,3	310	1240	1,070	240
ROCKMASTER2PLUS-16	1"	25	25,4	35,1	37,8	240	960	1,590	300